
135R-103809 REV.: 3 4 1/2 -4 7/8 SEISMIC VERTICAL LIMIT-STOP, NUT AND WASHER, TIGHTEN TOGETHER (SEE NOTE 1 & 3) 3/8 OPERATING GAP - ELASTOMERIC ELEMENT (21/8)-1 DIA MAX ROD, NUT AND WASHER (SEE NOTE 1) - 3/8 MIN AT FREE POSITION SPRING (47/16)FREE **HEIGHT** SEISMIC VERTICAL LIMIT-STOP, 3/8 OPERATING NUT AND WASHER, TIGHTEN GAP TOGETHER (SEE NOTE 3)

REV. DESCRIPTION DATE BY

TYPE HRS-1E-D PRE-COMPRESSED ELASTOMERIC & SPRING HANGERS FOR 1" NOMINAL DEFLECTION								
HANGER	RATED LOAD (LBS)	DEFLECTION (IN)	SPRING RATE (LB/IN)	SPRING COLOR CODE	ELEMENT LOAD & COLOR CODE			
HRS-1E-D400PR	400	1.70	303	BLACK	RE-D-750 BLACK			
HRS-1E-D650PR	650	1.44	619	RED	RE-D-750 BLACK			
HRS-1E-D825NPR ¹	825	1.56	771	RED/DK BLUE	RE-D-750 BLACK			
HRS-1E-D1000PR	1000	1.37	1000	TAN	RE-D-1350 RED			
HRS-1E-D1400PR	1400	1.52	1400	PINK	RE-D-1350 RED			
HRS-1E-D2000PR	2000	1.62	1800	WHITE	RE-D-1900 GREEN			

NOTES:

1. TWO NESTED SPRINGS YIELD THIS LOAD. THE COLOR CODE INDICATED IS FOR OUTER SPRING/INNER SPRING.



ISOLATOR SELECTIONS					
LOC 1:	LOC 2:				
LOC 3:	LOC 4:				
LOC 5:	LOC 6:				
LOC 7:	LOC 8:				
CUSTOMER EQP'T. TAG:					

NOTE: MATERIAL SHOWN IS FOR (1) SET.

NOTES:

- 1. HANGER RODS, NUTS AND WASHERS, AS SHOWN, NOT BY THE VMC GROUP.
- 2. STANDARD FINISH: HANGER BOX PAINTED, POWDER COATED OR GALVANIZED STEEL, SPRING POWDER COAT.
- 3. SEISMIC VERTICAL LIMIT-STOP HARDWARE REQUIRED FOR SEISMIC APPLICATIONS.
- 4. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER AT TIME OF ORDER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS
- 8. HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION.
- 9. DOUBLE LOWER NUT PROVIDED.
- 10.ROD EXTENSION BELOW LOWER NUT EXTENDS (1.5XROD DIA.) AS SHIPPED.
- 11.PRE-COMPRESSED 50% OF SPRING RATED DEFLECTION.
- 12.RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:	MODEL HRS-1E-D 400-2000 LBS.		SCALE : NONE	Membe, V.V.
JOB NAME:			SHEET:	
CUSTOMER:	PRE-COMPRESSED ELASTOMERIC AND SPRING HANGERS	VMC	1 OF 1	
CUSTOMER P.O.:	1 INCH DEFLECTION	GROUP THE POWER OF TOGETHER	DRAWING NO.:	REVISION
SALES ORDER:	THISTIBLI LEGITOR	Bloomingdale, NJ 07403 Houston, TX 77041		