3 1/2 SEISMIC VERTICAL LIMIT-STOP, NUT AND WASHER, TIGHTEN TOGETHER (SEE NOTE 1 & 3) 1 DIA MAX ROD, NUT AND WASHER (SEE NOTE 1) 3/8 MIN AT FREE POSITION ELASTOMERIC WASHER 10 1/8 (BY THE VMC GROUP) (43/8)FREE **HEIGHT** SPRING 3/8 OPERATING SEISMIC VERTICAL LIMIT-STOP, NUT AND WASHER, TIGHTEN TOGETHER (SEE NOTE 3)


TYPE HSA-1E PRE-COMPRESSED SPRING ANGULARITY HANGERS FOR 1"							
NOMINAL DEFLECTION							
HANGER	RATED LOAD	DEFLECTION	SPRING RATE	SPRING			
	(LBS)	(IN)	(LB/IN)	COLOR CODE			
HSA-1E-195PR	195	1.95	100	DK BLUE			
HSA-1E-400PR	400	1.32	303	BLACK			
HSA-1E-650PR	650	1.05	619	RED			
HSA-1E-1000PR	1000	1.00	1000	TAN			
HSA-1E-1400PR	1400	1.00	1400	PINK			
HSA-1E-2000PR	2000	1.11	1802	WHITE			

DESCRIPTION

DATE

BY

REV.



NOTES:

1. HANGER RODS, NUTS AND WASHERS, AS SHOWN, NOT BY THE VMC GROUP. INSTALL WASHER .16 THK. MIN. X 3 O.D. MIN. WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS.

- STANDARD FINISH: HANGER BOX PAINTED, POWDER COATED OR GALVANIZED STEEL, SPRING - POWDER COAT.
- 3. SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS.
- 4. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.
- 8. DOUBLE LOWER NUT PROVIDED.

SALES ORDER:

135R-103827 REV.: 2

- 9. ROD EXTENSION BELOW LOWER NUT EXTENDS (1.5XROD DIA.) AS SHIPPED.
- 10.PRE-COMPRESSED 50% OF SPRING RATED DEFLECTION.
- 11.RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

ISOLATOR SELECTIONS			
LOC 1:	LOC 2:		
LOC 3:	LOC 4:		
LOC 5:	LOC 6:		
LOC 7:	LOC 8:		
CUSTOMER EQP'T. TAG:	•		

NOTE: MATERIAL SHOWN IS FOR (1) SET.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:		
JOB NAME:		
CUSTOMER:		
CUSTOMER P.O.:		

MODEL HSA-1E 195-2000 LBS.
PRE-COMPRESSED
SPRING ANGULARITY HANGERS
1 INCH DEFLECTION

	SHI
THE VMC GROUP	DR
The Power of Together	
Bloomingdale, NJ 07403	
Houston, TX 77041	

SCALE:	
NONE	Member
SHEET:	-VISCM
1 OF 1	

RAWING NO.: REVISION