
135R-103828 REV.: 2 3 1/2 SEISMIC VERTICAL LIMIT-STOP, NUT AND WASHER, TIGHTEN TOGETHER (SEE NOTE 1 & 3) 1 DIA MAX ROD, NUT AND WASHER (SEE NOTE 1) - 3/8 MIN AT FREE POSITION ELASTOMERIC WASHER (BY THE VMC GROUP) 10 1/8 (51/2)FREE -SPRING HEIGHT 3/8 OPERATING SEISMIC VERTICAL LIMIT-STOP, GAP NUT AND WASHER, TIGHTEN TOGETHER (SEE NOTE 3)

REV.	DESCRIPTION	DATE	BY

TYPE HSA-2D PRE-COMPRESSED SPRING ANGULARITY HANGERS FOR 2" NOMINAL DEFLECTION							
HANGER	RATED LOAD (LBS)	DEFLECTION (IN)	SPRING RATE (LB/IN)	SPRING COLOR CODE			
HSA-2D-75PR	75	2.42	31	WHITE			
HSA-2D-160PR	160	2.29	70	YELLOW			
HSA-2D-230PR	230	2.30	100	GREEN			
HSA-2D-355PR	355	2.15	165	DK BROWN			
HSA-2D-435PR	435	1.89	230	RED			
HSA-2D-725PR	725	1.61	450	TAN			
HSA-2D-845PR	845	1.48	570	PINK			



NOTES:

- 1. HANGER RODS, NUTS AND WASHERS, AS SHOWN, NOT BY THE VMC GROUP. INSTALL WASHER .16 THK. MIN. X 3 O.D. MIN. WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS.
- 2. STANDARD FINISH: HANGER BOX PAINTED, POWDER COATED OR GALVANIZED STEEL, SPRING - POWDER COAT.
- 3. SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS.
- 4. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER. CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.
- 8. DOUBLE LOWER NUT PROVIDED.

SALES ORDER:

- 9. ROD EXTENSION BELOW LOWER NUT EXTENDS (1.5XROD DIA.) AS SHIPPED.
- 10.PRE-COMPRESSED 50% OF SPRING RATED DEFLECTION.
- 11. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

ISOLATOR SELECTIONS				
LOC 1:	LOC 2:			
LOC 3:	LOC 4:			
LOC 5:	LOC 6:			
LOC 7:	LOC 8:			
CUSTOMER EQP'T. TAG:				

NOTE: MATERIAL SHOWN IS FOR (1) SET.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:		
JOB NAME:		
CUSTOMER:		
CUSTOMER P.O.:		

MODEL HSA-2D 75-845 LBS. PRE-COMPRESSED SPRING ANGULARITY HANGERS 2 INCH DEFLECTION

		NONE	Memper	
		1 OF 1		
	THE VMC GROUP The Power of Together Bloomingdale, NJ 07403 Houston, TX 77041	DRAWING NO.:		REVISION