**ISOLATOR ISOLATOR** #1 VARIES ANCHOR BOLT TEMPLATE **ISOLATOR** DIMENSION (LENGTH) VARIES ANCHOR BOLT TEMPLATE **ISOLATOR** REINFORCING STEEL **ISOLATOR ISOLATOR** BASE DIMENSION (WIDTH) MODULAR SIDE RAIL MINIMUM EDGE DISTANCE ALL DIRECTIONS 11" OVERALL HEIGHT HOUSEKEEPING PAD L\_1" CLEARANCE

DESCRIPTION DATE REV.

	ļ	SOLA	TORS		
LOCATION		_ATOR YPE	COLOR CODE	RATED LOAD (lbs.)	RATED DEFL (in.)
1					
2					
3					
4					
5					
6					
EQUIPMEN	T / MOD	EL:			
CUST REF	DWG:				
		МОТ	OR		
FRAME SIZE:	I	HP	RPM	WT.	
		PUN	ИP		
SUCTION		DISCHAR	GE	WT.	
CONCRETE WT.			E WT.		
	TOTAL ISOLATED WT.				
TOTAL ESTIMATED SHIPPING WEIGHT:					
•		•			

TAG No.

QTY. REQ'D. \_\_\_\_\_

## NOTES:

211R-103516 REV.: 2

1. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL, HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:		
JOB NAME:		
CUSTOMER:		
CUSTOMER P.O.:		
SALES ORDER:		

MODEL MPF 10 INCH SEISMIC MODULAR POURING FORM INERTIA BASE 1 INCH DEFLECTION

THE VMC GROUP
The Power of Together

Houston, TX 77041

NONE

SHEET:



DRAWING NO.:

Bloomingdale, NJ 07403

REVISION