ISOLATOR ISOLATOR #1 VARIES VARIES ANCHOR BOLT TEMPLATE **ISOLATOR** DIMENSION (LENGTH) VARIES ANCHOR BOLT TEMPLATE **ISOLATOR** REINFORCING STEEL **ISOLATOR** VARIES **ISOLATOR** - BASE DIMENSION (WIDTH) MODULAR SIDE RAIL MINIMUM EDGE DISTANCE ALL DIRECTIONS 11" OVERALL HEIGHT HOUSEKEEPING PAD ☐ 1" CLEARANCE

DESCRIPTION REV. DATE

ISOLATORS						
_OCATION	ISOLATOR TYPE	COLOR CODE	RATED LOAD (lbs.)	RATED DEFL (in.)		
1						
2						
3						
4						
5						
6						
EQUIPMENT / MODEL:						
CUST REF DWG:						
MOTOR						
RAME SIZE:	HP	RPM	WT.			
PUMP						
SUCTION	DISCHARGE		WT.	WT.		
CONCRETE WT.						
TOTAL ISOLATED WT.						
TOTAL ESTIMATED SHIPPING WEIGHT:						

TAG No.

QTY. REQ'D. _____

NOTES:

RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

JER	D FO	R:

SALES ORDER:

211R-103781 REV.: 2

JOB NAME: CUSTOMER : _____

CUSTOMER P.O.:

MODEL MPF 10 INCH SEISMIC MODULAR POURING FORM INERTIA BASE 2 INCH DEFLECTION



NONE

SHEET



The Power of Together Bloomingdale, NJ 07403 Houston, TX 77041

REVISION